

TD-4258

POCT BLOOD GLUCOSE MONITORING SYSTEM



FEATURES

- Strip eject function
- USB data transmission
- Embedded barcode scanner
- Flexible Memory Capacity: 1000 Measurement Results, 2000 Operator ID, 500 QC
- Data Management and Analysis Supported by U-Right POCT Management System



SPECIFICATIONS

Enzyme Type	GDH-FAD
Sample Size	1.0 μ L
Reaction Time	5 seconds
Measurement Range	10~600mg/dL (0.55~33.3mmol/L)
Hematocrit Range	0 ~ 70%
Precision	SD < 5 mg/dL (0.278 mmol/L) at < 100mg/dL (5.55 mmol/L); CV < 5% at 100mg/dL (5.55 mmol/L)
Accuracy	\pm 15mg/dL if < 100mg/dL ; \pm 15% if \geq 100mg/dL
Ketone Warning	Yes
Communication	Mini-USB
Power Source	Li-ion Rechargeable Battery
Memory Capacity	1000 Measurement Results, 2000 Operator ID, and 500 QC
Dimension	122 (L) x 64 (W) x 24 (H) mm
Weight	130g (Without Battery)
Operating Condition	10°C (50°F) ~ 40°C (104°F)
Storage Condition	-20°C (-4°F) ~ 60°C (140°F) (Meter); 2°C (35.6°F) ~ 32°C (89.6°F) (Strip)
Units Per Carton	30
Carton Size	42.5 (L) x 32.5 (W) x 34.5 (H) mm
Cross Weight Per Carton	12.5 kg



www.taidoc.com

TaiDoc Technology Corp.

B1-7F., No.127, Wugong 2nd Rd., Wugu Dist.,
New Taipei City 24888, Taiwan
Tel : +886-2-6625-8188 Fax : +886-2-6625-0288