TD-4277

BLOOD GLUCOSE MONITORING SYSTEM

ISO 15197:2013

±15mg/dL&±15%

5 Sec, 0.5 µL

Display Screen

Strip-Ejection

Bluetooth®

FEATURES

- Strip port indicator
- Large and backlit display
- Before / After meal (AC/PC) presetable

iOS Android

ProCheck

ProCheck

SPECIFICATIONS

Enzyme Type	GDH-FAD
Sample Size	0.5 µL
Reaction Time	5 sec
Measurement Range	20~600mg/dL (1.1~33.3mmol/L)
Hematocrit Range	35% - 60%
Precision	SD < 5 mg/dL (0.278 mmol/L) at < 100mg/dL (5.55 mmol/L); CV < 5% at 100mg/dL (5.55 mmol/L)
Accuracy	±15mg/dL if < 100mg/dl ; ±15% if ≧ 100mg/dL
Ketone Warning	Yes
Communication	Mini USB (HID) / Bluetooth
Power Source	AAA * 2
Memory Capacity	1000 sets
Day Average	7, 14, 21, 28, 60, 90 Days
Daily Alarm	4 daily alarms
Dimension	96 (L) x 61 (W) x 26 (H)mm
Weight	67.2g (Without Battery)
Operating Condition	10°C(50°F) ~ 40°C(104°F), below 85% R.H.
Storage Condition	-20°C (-4°F) ~ +60°C (140°F) (Meter) 2°C(35.6°F)~32°C(89.6°F) (Strip)
Units Per Carton	30
Carton Size	405 (L) x 390 (W) x 365 (H) mm
Cross Weight Per Carton	12.2 kg

TaiDoc

TaiDoc Technology Corp.

B1-7F., No.127, Wugong 2nd Rd., Wugu Dist.,
New Taipei City 24888, Taiwan
Tel : +886-2-6625-8188 Fax : +886-2-6625-0288

www.taidoc.com