TD-4280

BLOOD GLUCOSE MONITORING SYSTEM

5 Sec, 0.5μL

Strip-Ejection

Voice Guidance

FEATURES

- Before / after meal (AC/PC) presetable
- Voice guidance for measuring result
- Ketone warning
- Display calendar and clock when meter standby

SPECIFICATIONS

Enzyme Type	GDH-FAD
Sample Size	0.5 μL
Reaction Time	5 seconds
Measurement Range	20 ~ 600mg/dL (1.1 ~ 33.3mmol/L)
Hematocrit Range	35%-60%
Precision	SD < 5 mg/dL (0.278 mmol/L) at < 100mg/dL (5.55 mmol/L); CV < 5% at 100mg/dL (5.55 mmol/L)
Accuracy	±15mg/dL if ≦100mg/dL; ±15% if >100mg/dL
Ketone Warning	Yes
Communication	RS232
Power Source	AAA x 2
Memory Capacity	450 sets
Day Average	7, 14, 21, 28, 60, 90 days
Daily Alarm	4 daily alarms
Dimension	95 (L) x 52 (W) x 20 (H) mm
Weight	48.8 g (without battery)
Operating Condition	10°C(50°F)~40°C(104°F)
Storage Condition	-20°C(-4°F) ~ +60°C(140°F) (Meter) 2°C(35.6°F)~32°C(89.6°F) (Strip)
Units Per Carton	30
Carton Size	405 (L) x 390 (W) x 365 (H) mm
Cross Weight Per Carton	7.3 kg

TaiDoc

TaiDoc Technology Corp.

B1-7F., No.127, Wugong 2nd Rd., Wugu Dist.,
New Taipei City 24888, Taiwan
Tel : +886-2-6625-8188 Fax : +886-2-6625-0288

www.taidoc.com